

DECLARATION OF PERFORMANCE No. 002 GOR
(Construction products regulation No. 305/2011)

1. Unique identification code of the product-type:

Dry pressed ceramic tile with water absorption $E_b > 10 \%$
Formats (mm): 200x400, 200x500, 250x400, 250x600, 250x750

2. Intended use:

Wall tile, indoor use

3. Manufacturer:

Gorenje Keramika, d.o.o.
Partizanska cesta 12,
3320 Velenje
Slovenija

4. Systems of assessment and verification of constancy of performance (AVCP system):

System 4

5. Harmonised technical specification

SIST EN 14411:2016

6. Declared performance :

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1	SIST EN 14411:2016
Breaking strenght	$\geq 600 \text{ N}$ (thickness $\geq 7,5 \text{ mm}$) $\geq 200 \text{ N}$ (thickness $< 7,5 \text{ mm}$)	
Flexural tensile strenght or modulus of rupture	$\geq 12 \text{ N/mm}^2$ (thickness $\geq 7,5 \text{ mm}$) $\geq 15 \text{ N/mm}^2$ (thickness $< 7,5 \text{ mm}$)	
Release of dangerous substances: - cadmium (Cd) - lead (Pb)	NPD NPD	
Termal shock resistance	passed	
Bond strenght/adhesion for: - cementitious adhesives - dispersion adhezives - reaction resin adhezives - mortar	NPD NPD NPD NPD	
Durability	passed	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
This declaration of performance is issued in accordance with Construction regulation No. 305/2011 under the sole responsibility of the manufacturer identified in point 3.

Signed for and on the behalf of the manufacturer by
Boris LAUBIČ, director

Velenje, 02nd March 2020

gorenje
Gorenje Keramika, d.o.o.
Velenje, Partizanska cesta 1.

Signature